




Material Safety Data Sheet

NFPA	WHMIS	PPE	Transport Symbol
	Non-controlled	 	Not regulated

Revision Date: 27-Mar-2012

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Idemitsu ATF Type TLS-LV, 12 x 1 Quart Case
Product Code: 10114-042B
Recommended use: Automotive Lubricant

Contact Manufacturer
Idemitsu Lubricants America,
701 Port Rd.
Jeffersonville, IN. 47130
Telephone: 812-285-8234
Fax: 812-285-8243
Contact Name: Robin Hutchens
Email: rhutchens@ilacorp.com

Emergency Telephone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

CAUTION!

Emergency Overview

Vapors may be irritating to eyes, nose, throat, and lungs

Appearance Clear Red Oily Liquid

Physical State: Liquid

Odor: Mild

Mexico - Grade Slight risk, Grade 1

Potential Health Effects

Principle Routes of Exposure Skin, Eye

Acute Effects

Eyes May cause slight irritation

Skin May cause skin irritation and/or dermatitis

Inhalation Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing

Ingestion May be harmful if swallowed

Chronic Effects

This product contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects

See Section 11 for additional Toxicological information.

Potential Environmental Effects

See Section 12 for additional Ecological information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.

Non-Hazardous Components

Chemical Name	CAS-No	Weight %
Lubricating Base Stocks	Mixture	>80

4. FIRST AID MEASURES

General Advice

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Inhalation

Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion

Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty lean forward to reduce the risk of aspiration. Swallowing small quantities of diluted product may cause nausea, diarrhea or abdominal distress. Consult a physician.

Protection of First-aiders

Use personal protective equipment. Avoid contact with skin, eyes and clothing.

5. FIRE-FIGHTING MEASURES

Flammable Properties

NFPA: Class IIIB Combustible Liquid

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Hazardous combustion products

Carbon oxides, Phosphorus compounds (POx), Sulphur oxides, Calcium Oxides (CaOx), Oxides of Boron.

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA **Health:** 1 **Flammability:** 1 **Instability:** 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with the skin and the eyes. Use personal protective equipment. Remove all sources of ignition. Avoid breathing vapors or mists. Ensure adequate ventilation.

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

Methods for Clean-up Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Pick up and transfer to properly labeled containers.

Spill Management

LARGE SPILLS Eliminate sources of ignition. Prevent additional discharge of material if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify the National Response Center.

WATER SPILLS Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations

7. HANDLING AND STORAGE

Handling Wear personal protective equipment. Do not breathe vapors or spray mist. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

Storage Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place.

Safe Handling Advice Handle in accordance with good industrial hygiene and safety practices.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Other Exposure Guidelines (If Generated)

Chemical Name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSH REL TWA	ILA IHG	ILA ROEG

Oil mist, mineral	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA 5 mg/m ³ ST 10 mg/m ³		
-------------------	--------------------------	--------------------------	--	--	--

Engineering measures

Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal Protective Equipment

Eye/face Protection

Safety glasses equipped with side shields are recommended as minimum protection in industrial settings.

Skin Protection

Wear protective gloves/clothing. Use clean protective clothing if splashing or spraying conditions are present. Protective clothing may include long-sleeve outer garment, apron, or lab coat. **Glove Type:** Neoprene. nitrile rubber. Nitriles. butyl-rubber.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear Red Oily Liquid
Odor:	Mild
Physical State:	Liquid
Flash Point	172°C / 342°F
Method	COC ASTM D92
Density	0.85 g/cm ³ @15°C
Viscosity	@ 40C = 23.12 cSt; @ 100C = 5.338 cSt

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended storage conditions. Hazardous polymerization does not occur.
Conditions to Avoid	Heat, flames and sparks
Incompatible Materials	Strong oxidizing agents.
Hazardous decomposition products	Thermal decomposition can lead to release of irritating gases and vapors

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

LD50 Oral:	> 10,000 mg/kg
LD50 Dermal:	> 4,000 mg/kg

LC50 Inhalation: >11,000 mg/m³ (dust)
LC50 Inhalation: > 10,000 ppm (vapor)

Chronic Toxicity

Carcinogenicity:

The petroleum base oils contained in this product have been highly refined by a variety of processes including solvent extraction, hydrotreating, and dewaxing to remove aromatics and improve performance characteristics. All of the oils meet the IP-346 criteria of less than 3 percent PAH's and therefore none are listed as a carcinogen by NTP, IARC, or OSHA

12. ECOLOGICAL INFORMATION

Ecotoxicity

Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment. This material contains phosphorus which is a controlled element for disposal in effluent waters in most sections of North America. Phosphorus is known to enhance the formation of algae. Severe algae growth can reduce oxygen content in the water possibly below levels necessary to support marine life.

Lubricant oil basestocks are complex mixtures of hydrocarbons (primarily branched chain alkanes and cycloalkanes) ranging in carbon number from C15 to C50. The aromatic hydrocarbon content of these mixtures varies with the severity of the refining process. White oils have negligible levels of aromatic hydrocarbons, whereas significant proportions are found in unrefined basestocks. Olefins are found only at very low concentrations. Volatilization is not significant after release of lubricating oil basestocks to the environment due to the very low vapor pressure of the hydrocarbon constituents. In water, lubricating oil basestocks will float and will spread at a rate that is viscosity dependent. Water solubilities are very low and dispersion occurs mainly from water movement with adsorption by sediment being the major fate process. In soil, lubricating oil basestocks show little mobility and adsorption is the predominant physical process.

Both acute and chronic ecotoxicity studies have been conducted on lubricant base oils. Results indicate that the acute aquatic toxicities to fish, Daphnia, Ceriodaphnia and algal species are above 1000 mg/l using either water accommodated fractions or oil in water dispersions. Since lubricant base oils mainly contain hydrocarbons having carbon numbers in the range C15 to C50, it is predicted that acute toxicity would not be observed with these substances due to low water solubility. Results from chronic toxicity tests show that the no observed effect level (NOEL) usually exceeds 1000 mg/l for lubricant base oils with the overall weight of experimental evidence leading to the conclusion that lubricant base oils do not cause chronic toxicity to fish and invertebrates.

Large volumes spills of lubricant base oils into water will produce a layer of undissolved oil on the water surface that will cause direct physical fouling of organisms and may interfere with surface air exchange resulting in lower levels of dissolved oxygen. Petroleum products have also been associated with causing taint in fish even when the latter are caught in lightly contaminated environments. Highly refined base oils sprayed onto the surface of eggs will result in a failure to hatch

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Conditions of use may cause this material to become a "hazardous waste", as defined by federal or state regulations. It is the responsibility of the user to determine if the material is a "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact your regional US EPA office for guidance concerning case specific disposal issues. Empty drums and pails retain residue. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose this product's empty container to heat, flame, or other ignition sources. DO NOT attempt to clean it. Empty drums and pails should be drained completely, properly bunged or sealed, and promptly sent to a reconditioner.

Contaminated Packaging

Clean container with water. Empty containers should be taken for local recycling, recovery or waste disposal.

14. TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

All components in the product are on the following Inventory Lists: U.S.A. (TSCA), Canada (DSL/NDL), China (IECSC).

Hazardous Components

USA

Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical Name	CAS-No	Weight %	RQ	TPQ
---------------	--------	----------	----	-----

Benzene	71-43-2	<0.05	10 lb final RQ 4.54 kg final RQ
---------	---------	-------	------------------------------------

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any HAPs.

Chemical Name	CAS-No	Weight %
Benzene	71-43-2	<0.05

State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	Weight %	California Prop. 65	Safe Harbor Limits for Reproductive Toxicity (MADLS)	Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Benzene	71-43-2	<0.05	Carcinogen Developmental Male Reproductive	24µg/dayoral 49µg/dayinhalation	6.4 µg/day oral 13 µg/day inhalation

State Right-to-Know

This product does not contain any substances regulated by state right-to-know regulations.

Predominant Ingredients - NJRTK

Chemical Name	CAS-No
Petroleum distillates, hydrotreated middle	64742-46-7
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based, contg. solvent deasphalted residual oil	72623-84-8
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	72623-86-0
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0
Alkenyl dicarboxylamide	ACC#147376

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

Non-controlled

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 27-Mar-2012

Revision Summary:

Disclaimer:

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet