



MATERIAL SAFETY DATA SHEET

US Continental
310 Reed Circle
Corona, CA 92879
Date Prepared: 6/18/09
US Continental

SECTION 1 - PRODUCT IDENTIFICATION

Product Name: K&N Red Air Filter Oil, part# 99-0533, 99-0551
Chemical Name: Oil, n.o.s.
Common Name: Petroleum Oil
Cas #: Mixture

SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

Common Name / Chemical Name CAS # %
Hydrotreated heavy paraffinic distillate 64742-54-7 <100
Xylene 1330-20-7 <1
Methyl lardate 68082-78-0 <2
Contains no other ingredients now known to be hazardous as defined by OSHA 29 CFR 1910.1000(z).

SECTION 3 – HAZARD IDENTIFICATION

Principle Hazards: Prolonged or repeated skin contact may cause dermatitis.
See section 11 for complete health hazard information
Threshold Limits: The PEL (OSHA) and the TLV (ACGIH) is 5 mg/m3 for oil mists.
Primary Routes of Exposure:
EYE May cause eye irritation if splashed into eyes.
SKIN Repeated or prolonged contact with skin may cause irritation, which may lead to various skin disorders. Avoid prolonged skin contact.
INHALATION Inhalation of vapor or oil mist from this product may cause mild irritation of the respiratory system.
Use in well ventilated areas.
ORAL Ingestion may cause nausea, diarrhea and stomach discomfort.

SECTION 4 – FIRST AID MEASURES

ORAL DO NOT INDUCE VOMITING. If conscious, give 2 glasses of water. Get immediate medical attention.
EYE Flush with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
SKIN Wash immediately with soap and water. Remove soiled clothing. Get medical attention if irritation Develops. Launder contaminated clothing.
INHALATION Remove exposed person to fresh air. If breathing is labored, administer oxygen and obtain immediate Medical attention.

Air Filter Oil

Date Prepared: 6-30-06 Page: 2

SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT: >200° C (COC) >392° F May release flammable vapors when heated above the flash point.
EXTINGUISHING MEDIA Carbon dioxide, dry chemical or foam. Avoid using water.

HAZARDOUS EXPOSURE Carbon monoxide and asphyxiants.

SPECIAL FIRE PROCEDURES Recommend SCBA. Use water only for cooling container. Water may cause splattering, or transport the flame.

=====**Section 6 – ACCIDENTAL RELEASE MEASURES**=====

Evacuate all non-essential personnel. Personal protective equipment must be worn, see PPE section 8 & 16. Remove

sources of ignition. Prevent entry into sewers and waterways. Contain release, pick up free liquid for recycling or disposal. Residual liquid can be absorbed with inert material. Check DOT / CERCLA and other agencies for reporting requirements.

Prevent contamination to soil, waterway and sewer systems.

=====**Section 7 – HANDLING AND STORAGE**=====

HANDLING Avoid prolonged skin contact, breathing vapors, and contaminated clothing. Use with adequate ventilation. Wear recommended protective equipment. Practice good personal hygiene after handling.

Empty containers retain material residue. Do not cut, weld, braze, solder or expose containers to other ignition sources.

STORAGE Store in closed containers of proper construction. Store away from ignition sources and in areas of good ventilation.

=====**Section 8 – EXPOSURE CONTROLS – PERSONAL PROTECTION**=====

EXPOSURE LIMITS: TLV = 5 mg/m³ as oil mist

VENTILATION: Use in areas of adequate ventilation. Use mechanical exhaust to control vapors or mists.

GLOVES: Nitrile or neoprene gloves are recommended.

EYE PROTECTION: Safety glasses, goggles, or a face shield are recommended.

RESPIRATORY: Use NIOSH/MSHA approved respirator with organic vapor cartridge and dust/mist cartridge is recommended if exposure limit is exceeded. Self-contained breathing apparatus is recommended for confined space entry.

CLOTHING: Long sleeve shirt and an apron is recommended when potential for skin contact is present. Wear neoprene or nitrile rubber boots when necessary to avoid contaminating shoes.

=====**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**=====

APPEARANCE: Red oily liquid Ph: None detected

BOILING POINT: >300° C **SOLUBILITY:** Negligible

EVAPORATION POINT: Less than ether **SPECIFIC GRAVITY:** 0.8650

FLAMMABILITY: N/A **VAPOR DENSITY:** Heavier than air

FLASH POINT: >200° C **VAPOR PRESSURE:** <0.01mm Hg @ 20° C

ODOR: Petroleum VOC %: Nil

Air Filter Oil

Date Prepared: 6-30-06 Page: 3

=====**SECTION 10 – STABILITY AND REACTIVITY**=====

STABILITY: Material is normally stable at ambient temperature and pressure.

CONDITIONS TO AVOID: Oxidizing agents. Do not heat above the flash point.

POLYMERIZATION: Will not occur.

DECOMPOSITION: Carbon dioxide, carbon monoxide

=====**SECTION 11 – TOXICOLOGICAL INFORMATION**=====

ORAL TOXICITY: Swallowing material may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea and abdominal pain.

EYE IRRITATION: Not expected to cause eye irritation.

SKIN IRRITATION: Not expected to be a primary skin irritant. Prolonged or repetitive contact may cause irritation.

CARCINOGENIC: This material has not been identified as a carcinogen by NTP, IARC, or OSHA.

===== **SECTION 12 – ECOLOGICAL INFORMATION** =====

This material is expected to have adverse affects on marine and plant life. Spills may contaminate drinking water.

===== **SECTION 13 – DISPOSAL CONSIDERATIONS** =====

DISPOSAL: Consult federal, state and local regulations regarding disposal methods. Recycle used oil. Do not contaminate used oil with solvents or other chemicals.

===== **SECTION 14 – TRANSPORTATION INFORMATION** =====

See 49 CFR part 171.8 through 178.510 DOT SHIPPING NAME: Oil, n.o.s.

DOT HAZARD CLASS: Not Regulated **UN/NA NUMBER:** NA 1270 **GUIDE NUMBER:** 27 **IMDG CODE**

Materials classified as DOT Combustible liquids (Flash Point >141° F and <200° F) are not regulated by DOT in containers of 110 gallons, or less for domestic shipments.

===== **SECTION 15 – REGULATORY INFORMATION** =====

TSCA All components of this material are on the US TSCA inventory.

SARA 311 CAL PROP 65 Not listed

SARA 312 RCRA Not listed

SARA 313 contains <1 ppm xylene CERCLA Listed

===== **SECTION 16 - OTHER INFORMATION** =====

Health Fire Reactivity PPE

HMIS CODE: 1 1 0 C

NFPA CODE: 1 1 0

Precautionary labels: NA

ADDITIONAL COMMENTS:

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make their own determination of the suitability of the material for their particular purpose.