

ITW Permatex
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: 00+ 1+ 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: ANAEROBIC GASKET MAKER 50 ML
Item No: 51813
Product Type: Anaerobic

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
POLYURETHANE METHACRYLATE RESIN (MIXTURE)	50-70	Not listed	Not listed
POLYGLYCOL DIMETHACRYLATE 25852-47-5	10-30	Not listed	Not listed
TREATED SILICON DIOXIDE, SYNTHETIC, CRYSTALLINE-FREE 67762-90-7	5-15	10 mg/m ³	Not listed
2-HYDROXYETHYL METHACRYLATE 868-77-9	<5	Not listed	Not listed
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<3	Not listed	Not listed
ACRYLIC ACID 79-10-7	0.1-1.0	2 ppm	10 ppm; 30 mg/m ³

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. May cause skin sensitization. Note: This product does not contain microcrystalline silica.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: May cause redness to eyes and irritation to nasal passages. Repeated skin contact may cause allergic skin reactions.

Component	Weight%	NTP	ACGIH Carcinogens	IARC Carcinogen
ACRYLIC ACID 79-10-7	0.1-1.0		A4 - Not Classifiable as a Human Carcinogen	Group 3 Monograph 71, 1999; Supplement 7, 1987; Monograph 19, 1979

Aggravated Medical Condition: May aggravate preexisting dermatitis.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200°F TCC
Recommended Extinguishing Media: Carbon dioxide, Dry chemical, Foam
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus.
Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen
Unusual Fire/Explosion Hazards: None.

5. FIRE FIGHTING MEASURES

Lower Explosive Limit: n/d
Upper Explosive Limit: n/d

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store below 100°F. Keep in cool and dark place. Avoid direct sunlight.
Handling: Avoid prolonged skin contact. Keep away from eyes. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: Not required under normal use. In case of insufficient ventilation, wear suitable respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Red gel
Odor: Mild
Boiling Point: >300°F
pH: Does not apply
Solubility in Water: Slight
Specific Gravity: 1.08-1.18
VOC(Wt.%): 1.5%
Vapor Pressure: <5 mm Hg @ 25°C
Vapor Density (Air=1): >1
Evaporation Rate: n/d

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur
Incompatibilities: Strong oxidizers, Metal salts, heat and amines
Conditions to Avoid: Heat
Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)
U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name: Not regulated
Hazard Class: None
UN/ID Number: None

IATA (Air)

Proper Shipping Name: Not regulated
Class or Division: None
UN/ID Number: None

IMDG (Vessel)

Product Name: ANAEROBIC GASKET MAKER 50 ML

Item No. 51813

Proper Shipping Name: Not regulated
Hazard Class: None
UN Number: None
Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

DIMETHYLBENZYL HYDROPEROXIDE

California Proposition 65: No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: March 13, 2013

Revision Number: 4