

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

| | | |
|--|--|--|
| Ashland P.O. Box 2219 Columbus, OH 43216 | Regulatory Information Number Telephone Emergency telephone number | 1-800-325-3751 614-790-3333 1-800-ASHLAND (1-800-274-5263) |
| Product name | Maxlife™ FULL SYNTHETIC SAE 5W-30 HIGH MILEAGE MOTOR OIL | |
| Product code | VV179 | |

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

May cause slight skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: thyroid effects, mild, reversible liver effects

Carcinogenicity

Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous Components | CAS-No. / Trade Secret No. | Concentration |
|---|----------------------------|---------------|
| HYDROTREATED HEAVY PARAFFINIC BASE OIL | 64742-54-7 | >=60-<70% |
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 | >=20-<30% |
| DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC | 64742-65-0 | >=1.5-<5% |

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

| | | |
|------------------------------|------------|-----------|
| ZINC DIALKYL DITHIOPHOSPHATE | 68649-42-3 | >=1-<1.5% |
|------------------------------|------------|-----------|

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIREFIGHTING MEASURES

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Water spray

Hazardous combustion products

Aldehydes, carbon dioxide and carbon monoxide, Hydrocarbons, oxides of sulfur, nitrogen and phosphorus

Precautions for fire-fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

DISTILLATES (PETROLEUM), SOLVENT- DEWAXED HEAVY PARAFFINIC

64742-65-0

| | | | |
|---------|-----------------------------------|-------------------------|---------------------|
| OSHA Z1 | Permissible exposure limit | 500 ppm | |
| OSHA Z1 | Permissible exposure limit | 2,000 mg/m ³ | |
| NIOSH | Recommended exposure limit (REL): | 5 mg/m ³ | Mist. |
| NIOSH | Short term exposure limit | 10 mg/m ³ | Mist. |
| OSHA Z1 | Permissible exposure limit | 5 mg/m ³ | Mist. |
| ACGIH | time weighted average | 5 mg/m ³ | Inhalable fraction. |

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use. Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|---|
| Physical state | liquid |
| Boiling point/boiling range | 626 °F / 330 °C @ 1,013.33 hPa Calculated Phase Transition Liquid/Gas |
| Flash point | > 390 °F / > 199 °C Cleveland open cup |
| Lower explosion limit/Upper explosion limit | 1 %(V) / 6 %(V) |
| Vapour pressure | 1.333 hPa @ 68 °F / 20 °C Calculated Vapor Pressure |
| Density | 0.853 g/cm ³ |

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

None known.

Incompatible products

Acids, halogenated hydrocarbons, halogens, Strong oxidizing agents

Hazardous decomposition products

Aldehydes, carbon dioxide and carbon monoxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

Acute oral toxicity - Product : no data available

Acute oral toxicity - Components

HYDROTREATED HEAVY PARAFFINIC BASE OIL : LD 50: > 15 g/kg Species: Rat

HEAVY PARAFFINIC DISTILLATE : LD 50: > 15 g/kg Species: Rat

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC : LD 50: > 5,000 mg/kg Species: Rat

ZINC DIALKYL DITHIOPHOSPHATE : LD 50: 2,000 - 5,000 mg/kg Species: Rat

Acute inhalation toxicity

Acute inhalation toxicity - Product : no data available

Acute dermal toxicity

Acute dermal toxicity - Product : no data available

Acute dermal toxicity - Components

HYDROTREATED HEAVY PARAFFINIC BASE OIL : LD 50: > 5 g/kg Species: Rabbit

HEAVY PARAFFINIC DISTILLATE : LD 50: > 5 g/kg Species: Rabbit

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

| | |
|--|--|
| DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC | : LD 50: > 5,000 mg/kg Species: Rabbit |
|--|--|

| | |
|---------------------------------|--|
| ZINC DIALKYL DITHIOPHOSPHATE | : LD 50: > 2,000 mg/kg Species: Rabbit |
|---------------------------------|--|

Acute toxicity (other routes of administration)

| | |
|--|---------------------|
| Acute toxicity (other routes of administration) | : no data available |
|--|---------------------|

12. ECOLOGICAL INFORMATION

Biodegradability

| | |
|----------------------------|---------------------|
| Biodegradability - Product | : no data available |
|----------------------------|---------------------|

Bioaccumulation

| | |
|---------------------------|---------------------|
| Bioaccumulation - Product | : no data available |
|---------------------------|---------------------|

Ecotoxicity effects

Toxicity to fish

| | |
|----------------------------|---------------------|
| Toxicity to fish - Product | : no data available |
|----------------------------|---------------------|

Toxicity to daphnia and other aquatic invertebrates

| | |
|---|---------------------|
| Toxicity to daphnia and other aquatic invertebrates - Product | : no data available |
|---|---------------------|

Toxicity to algae

| | |
|--------------------------------|---------------------|
| Toxicity to algae - Product | : no data available |
|--------------------------------|---------------------|

Toxicity to bacteria

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

Toxicity to bacteria - : no data available
Product

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

REGULATION

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification

SARA 311/312 Classification

No SARA Hazards

SARA 313 Component(s)

| | |
|--|--------|
| ZINC DIALKYL DITHIOPHOSPHATE | 1.08 % |
| PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS | 0.53 % |

New Jersey RTK Label Information

| | |
|--|------------|
| HYDROTREATED HEAVY PARAFFINIC BASE OIL | 64742-54-7 |
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 |
| LUBRICANT ADDITIVE | |

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

| | |
|---|------------|
| DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC | 64742-65-0 |
| ZINC DIALKYL DITHIOPHOSPHATE | 68649-42-3 |
| DINONYL DIPHENYLAMINE | 36878-20-3 |

Pennsylvania RTK Label Information

| | |
|---|------------|
| HYDROTREATED HEAVY PARAFFINIC BASE OIL | 64742-54-7 |
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 |
| LUBRICANT ADDITIVE | |
| DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC | 64742-65-0 |

Notification status

| | |
|---|-------------------------|
| US. Toxic Substances Control Act | y (positive listing) |
| Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133) | y (positive listing) |
| Australia. Industrial Chemical (Notification and Assessment) Act | n (Negative listing) |
| New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand | n (Negative listing) |
| Japan. Kashin-Hou Law List | y (positive listing) |
| Korea. Toxic Chemical Control Law (TCCL) List | y (positive listing) |
| Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act | n (Negative listing) |
| China. Inventory of Existing Chemical Substances | q (quantity restricted) |

| | HMIS | NFPA |
|------------------|------|------|
| Health | 1 | 1 |
| Flammability | 1 | 1 |
| Physical hazards | 0 | |
| Instability | | 0 |
| Specific Hazard | -- | -- |

16. OTHER INFORMATION



SAFETY DATA SHEET

Page: 12

Revision Date: 10/26/2012

Print Date: 8/26/2013

MSDS Number: R0396487

Version: 6.9

Maxlife™ FULL SYNTHETIC SAE 5W-30
HIGH MILEAGE MOTOR OIL
VV179

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).